



For all walks of life.

Commercial Flooring Product Comparison

Designed with safety and durability in mind, Protect-All® flooring will help you put your best foot forward. It has proven to be a trusted commercial flooring solution that can handle the most demanding environments. Here's how Protect-All's physical properties and product offerings stand up to the most common competitive products.


Physical Properties

	Protect-All	QuarryTile*	Epoxy*	Altro Aquarius™
Coefficient of Friction (Dry)	ASTM D2047 0.88	ASTM C1208 0.80	0.5 – 0.6	ASTM D2047 0.88
Bacteria & Mildew Resistance	Yes	5% water absorption	0.6% water absorption	Yes
Fire Test	NFPA Type 1 Rated ASTM E648 Type 1 ASTM E662 < 450	Fire Tile	UL263, NEPA 251, ULC-S101	CAN/ULC-S102.2 Tested ASTM E648 Class I ASTM E662 < 450
Breaking Strength	ASTM 741 405 x 723 lbs.	ASTM C648 350 lbs.	ASTM C881 300 lbs.	N/A
Wear Layer	1/4"	1/4"	1/16"	2/25"



Product Offerings

	Protect-All	QuarryTile	Epoxy	Altro Aquarius™
Seams	5'	6"	Minimal	N/A
Overall Thickness	1/8" and 1/4"	1/4"	1/8" and 1/4"	2/25"
Recycled Content	90% post-industrial	50% post-consumer	10% post-consumer	10% post-consumer
Manufacturer Tech Support	Yes	Yes	Yes (varies)	Yes
Installation Training	Yes	Yes	No	Yes



*Various brands. Reference the Product Data Sheet for complete information.

For more information, give us a call or visit our website today.

800-544-9538
protect-allflooring.com



Manufactured by Oscoda Plastics®, Inc.
5585 North Huron Avenue | Oscoda, Michigan 48750
989.739.6900 phone | 989.739.1494 fax | oscodaplastics.com

*Oscoda Plastics" and "Protect-All" are registered trademarks owned by Oscoda Plastics, Inc.
Altro Aquarius is a trademark owned by Altro Limited Company.
Protect-All Flooring is proudly manufactured in the United States of America.
PA Product Comparison_Flyer ORIG:6.17.16 REV: 10.25.17 – OP140025